



Melt Point
ASTM D-2117
2,650°F (1,454°C)



www.techflex.com

FLAMMABILITY

Rating _____ Non Flammable

CHEMICAL RESISTANCE

1=No Effect 4=More Affected
2=Little Effect 5=Severely Affected
3=Affected

Aromatic Solvents _____	1
Aliphatic Solvents _____	1
Chlorinated Solvents _____	1
Weak Bases _____	1
Salts _____	2
Strong Bases _____	2
Salt Water 0-S-1926 _____	2
Hydraulic Fluid MIL-H-5606 _____	1
Lube Oil MIL-L-7808 _____	1
De-Icing Fluid MIL-A-8243 _____	1
Strong Acids _____	2
Strong Oxidants _____	2
Esters/Ketones _____	1
UV Light _____	1
Petroleum _____	1
Fungus ASTM G-21 _____	1
Halogen Free _____	Yes
RoHS _____	Yes

PHYSICAL PROPERTIES

Wire Thickness _____	.005-.010
ASTM D-204	
Flammability Rating _____	Non Flammable
Recommended Cutting _____	Shears
Colors _____	1
Wall Thickness _____	.013-.025
Abrasion _____	High
Specific Gravity ASTM D-792 _____	NA
Moisture Absorption _____	NA
% ASTM D-570	
Hard Vacuum Data _____	
ASTM E-595	
TML _____	.00
CVCM _____	.00
WVR _____	.00
Outgassing _____	Very Low



800.323.5140 • 973.300.9242 • fax: 973.300.9409
104 Demarest Road • Sparta, NJ 07871

