



## FLAMMABILITY

Rating \_\_\_\_\_ Non Flammable

## CHEMICAL RESISTANCE

1=No Effect      4=More Affected  
2=Little Effect    5=Severely Affected  
3=Affected

Aromatic Solvents _____	1
Aliphatic Solvents _____	1
Chlorinated Solvents _____	1
Weak Bases _____	1
Salts _____	1
Strong Bases _____	2
Salt Water <i>0-S-1926</i> _____	1
Hydraulic Fluid <i>MIL-H-5606</i> _____	1
Lube Oil <i>MIL-L-7808</i> _____	1
De-Icing Fluid <i>MIL-A-8243</i> _____	1
Strong Acids _____	5
Strong Oxidants _____	5
Esters/Ketones _____	1
UV Light _____	2
Petroleum _____	2
Fungus <i>ASTM G-21</i> _____	2
Halogen Free _____	Yes
RoHS _____	Yes

**Melt Point**  
*ASTM D-2117*  
449°F (232°C)

**Maximum Continuous**  
*MIL-I-23053*  
302°F (150°C)

**Minimum Continuous**  
-40°F (-40°C)



## PHYSICAL PROPERTIES

Monofilament Thickness \_\_\_\_\_ .005  
*ASTM D-204*  
Flammability Rating \_\_\_\_\_ Non Flammable  
Recommended Cutting \_\_\_\_\_ Shears  
Colors \_\_\_\_\_ 1  
Wall Thickness \_\_\_\_\_ .015-.025



800.323.5140 • 973.300.9242 • fax: 973.300.9409  
104 Demarest Road • Sparta, NJ 07871

