




## WATERWAY Edelstahl-Wellschlauch Stainless steel annular tube



**WS DN12 WW2019XX Material: 1.4404 / AISI 316L**

	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13
mtr/s	0	0,25	0,5	0,75	1	1.25	-1.50	-1.75	-2.0	-2.25	-2.50	-2.75	-3.0
lt/s	0	0,029	0,058	0,088	0,117	0.270	0.324	0.379	0.433	0.487	0.541	0.595	0.619
Δp Pascal mtr.	0	344	1377	3098	5918	5877	8531	11704	15407	19805	27839	40974	62317

Biegeradius min. statisch Bending radius min. static	mm	25	P1 / P2 Wellenbreite / pitch	mm	3,1 / 2,2
ØID Innendurchmesser / Inner Diameter	mm	12.56	Fläche / Surface Area	m²/mtr	0.0764
ØOD Außendurchmesser / Outer Diameter	mm	16.8	Gewicht / Weight	kg/m	0,090
w Wandstärke / Wall thickness	mm	0,15	Volumen / Volume	l/mtr	0,17
max. Betriebsdruck max. operating pressure	bar	10	min. Querschnittsfläche Section Area	mm²	117
Wellen/mtr. / pitch/mtr.		267	Medium Wasser Medium Water 20°C	kg/m²	1000

