




## WATERWAY Edelstahl-Wellschlauch Stainless steel annular tube



WS DN20 WW2039XX Material: 1.4404 / AISI 316L

	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13
mtr/s	0	0,25	0,5	0,75	1,00	1,25	1,50	1,75	2,00	2,25	2,50	2,75	3,00
lt/s	0	0,083	0,167	0,250	0,333	0,416	0,500	0,583	0,666	0,750	0,833	0,916	0,999
Δp Pascal mtr.	0	171	685	1542	2766	4398	6497	9140	12229	15969	20473	25690	31666

Biegeradius min. statisch Bending radius min. static	mm	40	P1 / P2 Wellenbreite / pitch	mm	3,1 / 1,9
Ø ID Innendurchmesser / Inner Diameter	mm	20,6	Fläche / Surface Area	m <sup>2</sup> /mtr	0,1380
Ø OD Außendurchmesser / Outer Diameter	mm	26,2	Gewicht / Weight	kg/m	0,195
w Wandstärke / Wall thickness	mm	0,18	Volumen / Volume	l/mtr	0,43
max. Betriebsdruck max. operating pressure	bar	10	min. Querschnittsfläche Section Area	mm <sup>2</sup>	333
Wellen/mtr. / pitch/mtr.		200	Medium Wasser Medium Water 20°C	kg/m <sup>2</sup>	1000

