




WATERWAY Edelstahl-Wellenschlauch Stainless steel annular tube

WS DN25 WW2049XX Material: 1.4404 / AISI 316L



	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13
mtr/s	0	0,25	0,5	0,75	1,00	1,25	1,50	1,75	2,00	2,25	2,50	2,75	3,00
lt/s	0	0,129	0,257	0,386	0,514	0,643	0,772	0,900	1,029	1,158	1,286	1,415	1,543
Δp Pascal mtr.	0	138	554	1245	2215	3491	5071	7082	9563	12795	16406	20590	26086

Biegeradius min. statisch Bending radius min. static	mm	50	P1 / P2 Wellenbreite / pitch	mm	3,1 / 2,2
ØID Innendurchmesser / Inner Diameter	mm	25,6	Fläche / Surface Area	m ² /mtr	0,1496
ØOD Außendurchmesser / Outer Diameter	mm	31,6	Gewicht / Weight	kg/m	0,235
w Wandstärke / Wall thickness	mm	0,20	Volumen / Volume	l/mtr	0,64
max. Betriebsdruck max. operating pressure	bar	10	min. Querschnittsfläche Section Area	mm ²	514
Wellen/mtr. / pitch/mtr.		187	Medium Wasser Medium Water 20°C	kg/m ²	1000

