




WATERWAY Edelstahl-Spiralrohr Stainless steel helical tube



SR DN25 WW1030XX Material: 1.4404 / AISI 316L
spannungsfrei gegläht / annealed

	-1	-2	-3	-4	-5	-6	-7	-8	-9	-10	-11	-12	-13
mtr/s	0	0,285	0,332	0,387	0,437	0,542	0,605	0,646	0,698	0,826	0,920	0,979	1,075
lt/s	0	0,199	0,232	0,270	0,305	0,378	0,422	0,451	0,487	0,576	0,642	0,683	0,750
Δp Pascal mtr.	0	194.7	287.4	398.6	519.1	834.3	1010.4	1195.8	1409.0	1881.8	2430.5	2720.7	3383.4

Biegeradius min. statisch Bending radius min. static	mm	45	P1 / P2 Wellenbreite / pitch	mm	6,25
Ø ID Innendurchmesser / Inner Diameter	mm	27	Fläche / Surface Area	m ² /mtr	0,15260
Ø OD Außendurchmesser / Outer Diameter	mm	32,1	Gewicht / Weight	kg/m	0,340
w Wandstärke / Wall thickness	mm	0,3	Volumen / Volume	l/mtr	0,73
max. Betriebsdruck max. operating pressure	bar	16	mittl. Querschnittsfläche Section Area	mm ²	697,11
Wellen/mtr. / pitch/mtr.		160	Medium Wasser Medium Water 20°C	kg/m ²	1000

