




WATERWAY Edelstahl-Wellenschlauch Stainless steel annular tube

WS DN32 WW2059XX Material: 1.4404 / AISI 316L



| | -1 | -2 | -3 | -4 | -5 | -6 | -7 | -8 | -9 | -10 | -11 | -12 | -13 |
|-------------------|----|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| mtr/s | 0 | 0,25 | 0,5 | 0,75 | 1 | 1,25 | 1,50 | 1,75 | 2,00 | 2,25 | 2,50 | 2,75 | 3,00 |
| lt/s | 0 | 0,223 | 0,446 | 0,669 | 0,892 | 1,114 | 1,337 | 1,560 | 1,783 | 2,006 | 2,229 | 2,452 | 2,675 |
| Δp Pascal mtr. | 0 | 110 | 441 | 992 | 1793 | 2871 | 4302 | 5992 | 8123 | 10656 | 13804 | 18386 | 25319 |

| | | | | | |
|---|-----|------|---|---------------------|-----------|
| Biegeradius min. statisch Bending radius min. static | mm | 60 | P1 / P2 Wellenbreite / pitch | mm | 3,4 / 2,3 |
| ØID Innendurchmesser / Inner Diameter | mm | 33,7 | Fläche / Surface Area | m ² /mtr | 0,2084 |
| ØOD Außendurchmesser / Outer Diameter | mm | 40,9 | Gewicht / Weight | kg/m | 0,36 |
| w Wandstärke / Wall thickness | mm | 0,22 | Volumen / Volume | l/mtr | 1,09 |
| max. Betriebsdruck max. operating pressure | bar | 10 | min. Querschnittsfläche Section Area | mm ² | 891 |
| Wellen/mtr. / pitch/mtr. | | 185 | Medium Wasser Medium Water 20°C | kg/m ² | 1000 |

